

ZAP™ SERIES LASER RANGEFINDER SPECIFICATIONS

MODEL		ZAP™ 1200	ZAP™ 1500	ZAP™ 1600	ZAP™ 2000
MAX RANGE		1200yd/m	1500yd/m	1600yd/m	2000yd/m
MIN RANGE	5yd	●	●	●	●
RESOLUTION	0.1 yd ≤ 199.9yd, 1 yd ≥ 200yd	●	●	●	●
UNIT	Yard (default) / Meter	●	●	●	●
MEASUREMENT MODES	Auto-First & Last Target Targets (default)	●	●	●	●
	Auto-Distance & Hight Measurements	●	●	●	●
	Auto-Distance & Elevation Measurements (±90°)	●	●	●	●
	Auto-Distance & Compass Measurements	●		●	●
	Auto-Scan, Auto-Rain, Auto-Fog	●	●	●	●
MEASUREMENT TIME	< 1s (<600yd) , < 2s (>600yd)	●	●	●	●
DIMENSIONS (LxWxH)		3.5 x 2.7 x 1.4 in	4 x 2.8 x 1.65 in	4.3 x 2.8 x 1.6 in	4.6 x 2.9 x 1.6 in
WEIGHT		7.4oz	7.7oz	7.7oz	8.1oz
BATTERY	CR2 (3V) x 1pc	●	●	●	●
TRIPOD ADAPTER		●	●	●	●
WATERPROOF		●	water resistant	●	●
PROTECTION	All-Around Rubber Armored	●	●	●	●
MAGNIFICATION		6.5x	7x	7x	7x
OBJECTIVE DIAMETER		15mm	22mm	22mm	22mm
FIELD-OF-VIEW (@1000yd)		330ft	366ft	366ft	366ft
EYE RELIEF		13.5mm	15mm	15mm	15mm
DIOPTER ADJUSTMENT		±3D	±4D	±4D	±4D